



Excellent water quality is a smart business decision.

When you install a G1 Reverse Osmosis system, you combine cost-effective system configuration, cost-minimizing operations, and reduced post-treatment costs. The G1 Reverse Osmosis system helps you reduce maintenance costs by reducing contaminants* from your water that affect taste and clog equipment. Control your installation costs by using a system configured for your unique needs. Keep your operating costs low by monitoring and changing the G1 RO settings with an easy-to-use electronic controller. Purchasing a G1 RO is more than a sound business decision-you improve the quality of life for your building.

The G1 RO is part of the Culligan Matrix Solutions™ that combine durable and efficient equipment, systems experience, and technical experts who understand your unique requirements. From planning your system to installing your water treatment equipment, Culligan Matrix Solutions offer options that help deliver the quality of water to meet your needs. Consult with a Culligan representative to create your solution.

*contaminants may not necessarily be in your water.

Culligan Matrix Solutions Advantages:

- Simple System Integration
- Global Product Platform
- Flexible Configurations
- Quick Delivery/Easy Installation
- Exclusive Culligan Advanced Electronics
 - Historical Operating Data
 - Alarm Recognitions
 - US Standard and Metric Readings
 - Remote Monitoring Options
 - Telemetry Options

EXAMPLES OF MARKETS SERVED:

- AGRICULTURE
- ASSISTED LIVING
- AUTOMOTIVE
- BIO-PHARMACEUTICAL
- BOTANICALS
- BOTTLED WATER PLANTS
- CASINOS
- CHEMICAL PROCESSING
- COMMERCIAL BUILDINGS
- DAIRIES
- EDUCATIONAL FACILITIES
- ENERGY/POWER/COGENERATION
- ELECTRONICS
- GOVERNMENT
- GROCERY
- FOOD/BEVERAGE
- HEALTH CLUBS
- HOTELS/LODGING
- HOSPITALS/HEALTHCARE
- INK/DYE PRODUCTION
- LABORATORIES
- LAUNDRY
- MANUFACTURING
- MARINE
- MILITARY
- MULTI-UNIT HOUSING
- MUNICIPALITIES
- PLATING/COATING
- PRINTING
- PULP/PAPER
- OIL/PETROLEUM/GAS
- TEXTILE
- THEME PARKS
- UNIVERSITIES
- VEHICLE WASH



Pre-Treatment
Solutions



**Membrane
Solutions**



Deionization
Solutions



Storage
Solutions



Distribution
Solutions

System Specifications

Specification	US	Metric
Inlet Pressure (dynamic)	20 – 50 psig	1.4 – 3.5 bar
Maximum Operating Pressure	95 – 152 psig	6.6 – 10.5 bar
Power Voltage Frequency Phase	115 V 60 Hz 1	220 V 50 Hz 1
Feed Water Temperature	33 – 100° F	1 – 38° C
Turbidity, maximum	< 1 NTU	< 1 NTU
pH Range	6 – 11	6 – 11
Chlorine, max.	0 mg/l	0 mg/l
Total Dissolved Solids, max.	2500 mg/l	2500 mg/l
Silt Density Index Well Water Surface Water	< 3 < 5	< 3 < 5
Iron, maximum	< 0.1 mg/l	< 0.1 mg/l
Salt Rejection, nominal	> 98 %	> 98 %
Product Water Hardness	< 1% Raw Hardness	< 1% Raw Hardness

Examples of RO Applications

- Ice Production/Drinking Water - Reduces scaling, improves taste and clarity
- Steam Production - Reduces scaling and maintenance
- Humidification - Reduces scaling and dusting
- Misting - Reduces scaling and helps extend equipment life
- Pretreatment for High Purity Systems - Reduces regeneration requirements
- Reclaim/Recycling - Water conservation
- Washing and Rinsing - Improves performance, spot-free rinse

Standard Features

- Wall Mount Design
- Rotary Vane Pump
- Inlet Solenoid Valve
- Pretreatment Sediment Filter
- Concentrate and Recirculation Throttling Valves
- Pressure Indicators
- FRP Membrane Housings
- Electronic Turbine Style Flow Meters
- Culligan Electronic Control Panel
 - Telemetric Capability
 - Comprehensive System Monitoring
 - Lighted Alphanumeric Display
 - TDS Monitoring of Water Quality
 - Low Pressure Switch and Auto Restart
- Connection for Pretreatment Signal Switch and Level Control
- Elapsed run time monitor
- Visual Alarms
- Remote Alarm Output Connection
- System Flow Rate Monitoring
- User Selectable Flush Options
- 220 V/50 Hz

Optional Features & Accessories

- Leak Sensor
- Multi-Stage Pretreatment Filters
- Wireless Remote Digital Display
- RS232, RS485 Output
- Storage Tanks
- Level Controls
- Chemical Feed Pumps
- Ultraviolet Sterilization
- Pressurized Storage System
- Floor Stand
- Global Power Platform
- Additional Customization Available on Request

G1 Plus Reverse Osmosis System

Model	Nominal Capacity* (gpm/lpm)	Nominal Capacity* (gpd/m ³ /h)	Module Qty & Size	Nominal System Recovery (%)	Motor HP - kW	Dimension L x W x H (inches – millimeters)
G1-2S	0.35	500	(2), 2.5" x 21"	50	1/3	37 x 10 x 37.75
	1.31	0.08			0.25	940 x 254 x 959
G1-3S	0.52	750	(3), 2.5" x 21"	50	1/3	37 x 10 x 37.75
	1.97	0.12			0.25	940 x 254 x 959
G1-2L	0.83	1200	(2), 2.5" x 40"	50	3/4	37 x 10 x 46.25
	3.15	0.19			0.56	940 x 254 x 1175
G1-3L	1.18	1700	(3), 2.5" x 40"	50	3/4	37 x 10 x 46.25
	4.47	0.27			0.56	940 x 254 x 1175
G1-4L	1.53	2200	(4), 2.5" x 40"	50	3/4	37 x 10 x 46.25
	5.78	0.35			0.56	940 x 254 x 1175

*Nominal capacity based on new RO membranes operating on a properly pretreated feed water of 500 ppm TDS as NaCl, 77 °F (25 °C), Silt Density Index (SDI) below 3, and supplying water to atmosphere. Productivity will vary depending on the actual feed water quality and temperature.

Cat. No. BU0175/09-2012

Finally, an end-to-end solution from a single source.



Place your commercial and industrial water treatment needs in the hands of a global leader.

For over 75 years, Culligan has made better water. Our global network, comprised of 800+ dealers and international licensees in over 90 countries, is dedicated to addressing your water-related problems. As a worldwide leader in water treatment, our sales representatives and service technicians are familiar with the local water conditions in your area. Being global and local position us to deliver customized solutions to commercial and industrial water issues that affect your business and your bottom line.

QUALITY SYSTEM CERTIFIED ACCORDING TO UNI EN ISO 9001:2008 NORM

CULLIGAN ITALIANA SpA

40057 Cadrano di Granarolo dell'Emilia (BO) ITALY • Via Gandolfi, 6 • Tel. +39 051.601.7111 • Fax +39 051.76.56.02 • culligan@culligan.it • www.culligan.it

Culligan reserves the right to change any technical or design specifications for the models shown in this brochure.

Culligan Guarantee – Any manufacturing defects and corrosion are covered by the Culligan guarantee's norms.

better water. pure and simple.®